

PAGE 3/7 \* RCVD AT 2/24/2005 3:01:47 PM [Eastern Standard Time] \* SVR:USPTO-EFXRF-1/5 \* DNIS:8720306 \* CSID:17818639931 \* DURATION (mm-ss):03-26

Re: Patent No. 6,625,811  
Response filed February 24, 2005  
Reply to Notice of February 13, 2005

centering the structure of interest within the image of the specimen.

7. (Currently Amended) An arrangement for controlling analytical and adjustment operations of a microscope comprising:

multiple detectors for converting optical signals into electrical signals;

an electronic acquisition system, which converts the electrical signals coming from the detectors into digital signals and preprocesses them, is provided;

a PC, which receives the digital signals from the electronic acquisition system **and** identifies from the digital signals a graphical depiction which corresponds to an image of the specimen;

a display, which reproduces the graphical depiction and moreover offers selectable adjustment functions to the user, is connected to the PC;

an input unit is provided for choosing the adjustment functions and selecting at least one structure of interest in the image of the specimen; and

an electronic control system, with which the adjusting elements of the microscope are be controlled, is connected to the PC, wherein the arrangement is adapted to the automatic focusing of the structure of interest within an identified image of the specimen.

8. (Original) The arrangement as defined in claim 7, wherein the electronic control system has a memory that serves for temporary storage of the at least one structure of interest and is connected via a line to a routing unit; and a pixel clock is in communication both with the memory and with the routing unit.

9. (Original) The arrangement as defined in claim 8, wherein the routing unit has multiple outputs by way of which the microscope is controllable.

10. (Original) The arrangement as defined in claim 7, wherein the electronic acquisition system has multiple analog/digital converters that are connected to an electronic circuit.

Application Number: 2005/017,741

Response Date: February 24, 2005

Reply to Notice of February 13, 2005

11. (Original) The arrangement as defined in claim 10, wherein the electronic circuit is configured as an FPGA.

12. (Original) The arrangement as defined in claim 7, wherein the adjustment functions are arranged on the display in a panel box in the form of multiple click buttons.

13. (Currently Amended) A software program on a data carrier for controlling analytical and adjustment operations of a microscope, wherein the following processes are carried out:

depicting a data set in graphical form on a display associated with the microscope;  
selecting at least one position in the graphical form of the data set that depicts the image of the specimen;  
identifying automatically a region from the data set and the selected position; and  
performing an analytical or adjustment operation or both; and  
automatic focusing of a structure of interest within the identified image of the specimen.

14. (Original) The software program as defined in claim 13, wherein the analytical operation is based on the geometry of a structure of interest or on the data set of a structure of interest.

15. (Original) The software program as defined in claim 13, characterized by the step: selecting an adjustment function for execution of an adjustment operation.

16. (Original) The software program as defined in claim 15, wherein the adjustment operation modifies at least one image sensing parameter.

17. (Original) The software program as defined in claim 16, wherein the image sensing parameters consist essentially of zoom, image centering, detection sensitivity, illuminating light output, spectral composition of the illumination, polarization of the illumination, spectral detection of the identified region, and rotation of the identified

Application No. 08/552,012  
 Response dated: February 24, 2005  
 Reply to Notice of February 18, 2005

region.

18. (Original) The software program as defined in claim 13, comprising:  
     automatic focusing of a structure of interest within the identified image of the  
     specimen;  
     and centering of the structure of interest within the image of the specimen.